

Printing date 02.06.2015 *Version number* 20 *Revision:* 02.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP POWER BRAKE CLEANER
- · Article number: 090563
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400 *Fax:* +31 (0)561 694411

e-mail info@nl.motipdupli.com

- · Further information obtainable from: QHSE Department
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h 17:00h)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R38: Irritating to skin.



F+; Extremely flammable

R12: Extremely flammable.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

Printing date 02.06.2015 Version number 20 Revision: 02.06.2015

Trade name: MOTIP POWER BRAKE CLEANER

(Contd. of page 1)

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

Has a narcotising effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description

64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS

nr. 71-43-2)

- · Identification number(s)
- **EC** number: 265-151-9
- · Index number: 649-328-00-1
- · 3.2 Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 02.06.2015 Version number 20 Revision: 02.06.2015

Trade name: MOTIP POWER BRAKE CLEANER

| | (Cor | ntd. of page 2 |
|---|---|----------------|
| · Dangerous components: | | |
| CAS: 64742-49-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx | Naphtha (petroleum), hydrotreated light Xn R65 Xi R38 F R11 N R51/53 R67 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 | 75-100% |
| CAS: 124-38-9 EINECS: 204-696-9 | carbon dioxide Press. Gas L, H280 | 5-10% |
| · Additional information: For the | wording of the listed risk phrases refer to section 16. | |

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

 $See \ Section \ 8 \ for \ information \ on \ personal \ protection \ equipment.$

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 02.06.2015 Version number 20 Revision: 02.06.2015

Trade name: MOTIP POWER BRAKE CLEANER

(Contd. of page 3)

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

124-38-9 carbon dioxide

WEL Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Trade name: MOTIP POWER BRAKE CLEANER

· Eye protection: Not required.

(Contd. of page 4)

| 9.1 Information on basic physical an | d chemical properties |
|--|---|
| General Information | |
| Appearance: | |
| Form: | Aerosol |
| Colour: | Colourless |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/Melting range: | <-25 °C (<-13 °F) |
| Boiling point/Boiling range: | Not applicable, as aerosol. |
| Flash point: | < 21 °C (< 70 °F) |
| F | Not applicable, as aerosol. |
| Flammability (solid, gaseous): | Not applicable. |
| Ignition temperature: | > 200 °C (> 392 °F) |
| Decomposition temperature: | Not determined. |
| Self-igniting: | Product is not selfigniting. |
| Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 0.6 Vol % |
| Upper: | 7.0 Vol % |
| Vapour pressure at 20 °C (68 °F): | 5750 hPa (4313 mm Hg) |
| Density at 20 °C (68 °F): | $0.715 \text{ g/cm}^3 (5.967 \text{ lbs/gal})$ |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not applicable. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient (n-octanol/water | r): Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· Solvent content:

· EU-VOC in %:

· EU-VOC:

Organic solvents:

· 9.2 Other information

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

No further relevant information available.

94.0 %

672.1 g/l

94.00 %

(Contd. on page 6)

Printing date 02.06.2015 Version number 20 Revision: 02.06.2015

Trade name: MOTIP POWER BRAKE CLEANER

(Contd. of page 5)

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

| · LD/LC50 values | relevant for | classification: |
|------------------|--------------|-----------------|
|------------------|--------------|-----------------|

64742-49-0 Naphtha (petroleum), hydrotreated light

| Oral | | >5840 mg/kg (rat) |
|------------|-------------|----------------------|
| Dermal | LD50 | >2920 mg/kg (rabbit) |
| Inhalative | | >193 mg/m3 (rat) |
| | | 25.2 mg/l (rat) |
| | LC50 / 96 h | 11.4 mg/l (fish) |

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50 / 48 h | 3 mg/l (daphnia magna)

EC50 / 72 h | 30-100 mg/l (algae)

LC50 / 96 h | 93-117 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

GB

Trade name: MOTIP POWER BRAKE CLEANER

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue
 20 01 13* solvents
 15 01 04 metallic packaging
 - · Uncleaned packaging:
 - · Recommendation: Non contaminated packagings may be recycled.

| 14.1 UN-Number | |
|---------------------------------|---|
| ADR, IMDG, IATA | UN1950 |
| 14.2 UN proper shipping name | |
| ADR | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOU |
| IMDG | AEROSOLS (Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT |
| IATA | AEROSOLS, flammable |
| 14.3 Transport hazard class(es) | |
| ADR | |
| | |
| Class | 2 5F Gases. |
| Label | 2.1 |
| IMDG | |
| * | |
| Class | 2.1 |
| Label | 2.1 |
| IATA | |
| | |
| Class | 2.1 |
| Label | 2.1 |
| 14.4 Packing group | |
| ADR, IMDG, IATA | Void |
| 14.5 Environmental hazards: | |
| Marine pollutant: | Yes |
| Special marking (ADD). | Symbol (fish and tree) |
| Special marking (ADR): | Symbol (fish and tree) |

Trade name: MOTIP POWER BRAKE CLEANER

| | (Contd. of page |
|---|--|
| · Danger code (Kemler): · EMS Number: | - F-D,S-U |
| · 14.7 Transport in bulk according to Anne. MARPOL73/78 and the IBC Code | x II of Not applicable. |
| · Transport/Additional information: | |
| $\cdot ADR$ | |
| · Limited quantities (LO) | IL |
| · Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| · Transport category | 2 |
| · Tunnel restriction code | D |
| · IMDG | |
| · Limited quantities (LQ) | IL |
| · Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| · UN ''Model Regulation'': | UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY |
| - | HAZARDOUS |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- *H411 Toxic to aquatic life with long lasting effects.*
- R11 Highly flammable.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- *R65 Harmful: may cause lung damage if swallowed.*
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: R&D legislation and regulatory advisor
- · Contact: Mr. K. Smedeman
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015 Version number 20 Revision: 02.06.2015

Trade name: MOTIP POWER BRAKE CLEANER

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas L: Gases under pressure: Liquefied gas Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· * Data compared to the previous version altered.

(Contd. of page 8)